


AULA AU1.L2.1200.XY

Type: ceiling and wall lamp

Lampshade: acrylic glass

Light body: painted steel plate RAL 9016 (.41), RAL 7012 (.47), RAL Argento dorato (.70), RAL Copper (.72), RAL Bronze (.73), RAL Brass (.74)



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | IK06 | IK08 | Bluetooth | Emergency | Weight |
|----|------|-------------------------|----------------------------|------|-----|----|--------|------|------|-----------|-----------|--------|
| 42 | 4000 | 5932 | 5574 | 1200 | 125 | 50 | M | - | - | - | - | 3000 |

Lucis AU1.L2.1200.X AULA LED / LDC (Polar)

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 42 W

Color temperature: 4000 K

Module luminous flux: 5932 lm

Luminaire luminous flux: 5574 lm

A: 1200 mm

B: 125 mm

C: 50 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Not available

Track system: Not available

Sádrokarton: Not available

Weight: 3000 g

Luminaire: Lucis AU1.L2.1200.X AULA LED
Lamps: 1 x LED G6

