


ELIOS S7.K3.E120.XY

**Typ:** Deckenleuchte

**Lampenschirm:** Acrylglas

**Leuchte:** Aluminium lackiert – RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) oder RAL 9005 (.45)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	IK06	IK08	Bluetooth	Track-System	Sádrokarton	Gewicht
6,7	3000	899	727	120	63	M	-	-	-	-	-	500

**Spannung:** 230V

**IK Code:** IK06

**Vorschalgerät:** Driver

**CRI:** >90

**LED-Lebensdauer:** L80/F10 50000 Stunden

**Watt:** 6,7 W

**Farbtemperatur:** 3000 K

**Module luminous flux:** 899 lm

**Luminaire luminous flux:** 727 lm

**A:** 120 mm

**B:** 63 mm

**Dali 2:** Verfügbar

**Bewegungsmelder:** Nicht Verfügbar

**Notlichtmodul:** Nicht Verfügbar

**Bluetooth-Steuerung:** Nicht Verfügbar

**Track-System:** Nicht Verfügbar

**Sádrokarton:** Nicht Verfügbar

**Gewicht:** 500 g

Lucis S7.K3.E120.X ELIOS LED / LDC (Polar)

Luminaire: Lucis S7.K3.E120.X ELIOS LED  
Lamps: 1 x LED G5

