


ELIOS S7.K4.E120.XY

Type: ceiling lamp

Lampshade: acrylic glass

Light body: painted aluminium – RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) or RAL 9005 (.45)



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | DALI 2 | ☰ | ☷ | ☱ | ☲ | ☳ | ☴ | ☵ | ☶ | ☷ |
|-----|------|-------------------------------|----------------------------------|-----|----|-----------|---|---|---|---|---|---|---|---|-----|
| 6,7 | 4000 | 942 | 762 | 120 | 63 | M | - | - | - | - | - | - | - | - | 500 |

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 6,7 W

Color temperature: 4000 K

Module luminous flux: 942 lm

Luminaire luminous flux: 762 lm

A: 120 mm

B: 63 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Not available

Track system: Not available

Sádrokarton: Not available

Weight: 500 g

Lucis S7.K4.E120.X ELIOS LED / LDC (Polar)

Luminaire: Lucis S7.K4.E120.X ELIOS LED
Lamps: 1 x LED G5

