


MAIA PMMA S3.L1W.Y PA

Type: wall lamp

Lampshade: acrylic glass PMMA opal

Light body: white painted steel plate



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Motion sensor | Emergency module | Bluetooth | Scale | Weight |
|------|------|-------------------------|----------------------------|-----|-----|----|--------|---------------|------------------|-----------|-------|--------|
| 26,1 | 3000 | 3314 | 2978 | 150 | 500 | 75 | M | O* | P* | Q* | - | 1600 |

Lucis S3.L1W PA MAIA LED / LDC (Polar)

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 26,1 W

Color temperature: 3000 K

Module luminous flux: 3314 lm

Luminaire luminous flux: 2978 lm

A: 150 mm

B: 500 mm

C: 75 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 1600 g

Luminaire: Lucis S3.L1W PA MAIA LED
Lamps: 1 x LED G6

