

MAIA A ZKS.L1A.M500.Y




Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: white painted steel plate

Pendant: white cable

Driver of the luminaire is placed inside the ceiling rose (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
41,4	3000	6049	4985	150	500	2000	M	-	P*	Q*	-	D* 5000

Lucis ZKS.L1A.M500 MAIA LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 41,4 W

Color temperature: 3000 K

Module luminous flux: 6049 lm

Luminaire luminous flux: 4985 lm

A: 150 mm

B: 500 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Available on inquiry

Weight: 5000 g

Luminaire: Lucis ZKS.L1A.M500 MAIA LED
Lamps: 1 x LED G6

