

MAIA A ZKS.L3A.M500.Y

**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** white painted steel plate

**Pendant:** white cable

Driver of the luminaire is placed inside the ceiling rose (LED version).



| W    | K    | Module luminous flux lm | Luminaire luminous flux lm | A   | B   | C    | DALI 2 | Motion sensor | Emergency | Bluetooth | Track system | Weight |      |
|------|------|-------------------------|----------------------------|-----|-----|------|--------|---------------|-----------|-----------|--------------|--------|------|
| 31,3 | 3000 | 4754                    | 3918                       | 150 | 500 | 2000 | M      | -             | P*        | Q*        | R*           | D*     | 4600 |

Lucis ZKS.L3A.M500 MAIA LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 31,3 W

**Color temperature:** 3000 K

**Module luminous flux:** 4754 lm

**Luminaire luminous flux:** 3918 lm

**A:** 150 mm

**B:** 500 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Available on inquiry

**Sádrokarton:** Available on inquiry

**Weight:** 4600 g

Luminaire: Lucis ZKS.L3A.M500 MAIA LED  
Lamps: 1 x LED G6

