

MAIA A ZKS.L1A.M620.Y


Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: white painted steel plate

Pendant: white cable

Driver of the luminaire is placed inside the ceiling rose (LED version).



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Motion sensor | Emergency module | Bluetooth | Track system | Weight |
|------|------|-------------------------|----------------------------|-----|-----|------|--------|---------------|------------------|-----------|--------------|--------|
| 74,3 | 3000 | 9545 | 7919 | 220 | 620 | 2000 | M | - | - | Q* | - | 8200 |

Lucis ZKS.L1A.M620 MAIA LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 74,3 W

Color temperature: 3000 K

Module luminous flux: 9545 lm

Luminaire luminous flux: 7919 lm

A: 220 mm

B: 620 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 8200 g

Luminaire: Lucis ZKS.L1A.M620 MAIA LED
Lamps: 1 x LED G6

