


AULA AU3.L3.900.XY

Type: luminaire mural

Abat-jour: verre acrylique

Luminaire: tôle d'acier revêtue RAL 9016 (.41), RAL 7012 (.47), RAL Argento dorato (.70), RAL Copper (.72), RAL Bronze (.73), RAL Brass (.74)



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | ☺ | ☒ | ⚡ | 📄 | 🏷️ |
|------|------|-------------------------------|----------------------------------|-----|-----|----|-----------|---|---|----|---|------|
| 15,5 | 3000 | 2100 | 1973 | 920 | 120 | 95 | M | - | - | Q* | - | 2500 |

Lucis AU3.L3.900.X AULA LED / LDC (Polar)

Tension: 230V

IK code: IK06

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 15,5 W

Température Couleur: 3000 K

Module luminous flux: 2100 lm

Luminaire luminous flux: 1973 lm

A: 920 mm

B: 120 mm

C: 95 mm

Dali 2: Disponible

Capteur de mouvement: Non disponible

Module d'urgence: Non disponible

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 2500 g

Luminaire: Lucis AU3.L3.900.X AULA LED
Lamps: 1 x LED G6

