



IZAR II I2.L4.600.XY

Type: wall lamp

Lampshade: acrylic glass in combination with acrylic glass white (.92), black (.93) or stainless steel (.83)

Light body: white painted steel plate



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | IK06 | IP20 | LED | CRI >90 | Weight | |
|-----|------|-------------------------|----------------------------|-----|----|----|--------|------|------|-----|---------|--------|------|
| 9,1 | 4000 | 1278 | 1138 | 600 | 80 | 40 | M | - | - | Q* | - | - | 1400 |

Lucis I2.L4.600.X IZAR II LED / LDC (Polar)

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 9,1 W

Color temperature: 4000 K

Module luminous flux: 1278 lm

Luminaire luminous flux: 1138 lm

A: 600 mm

B: 80 mm

C: 40 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 1400 g

Luminaire: Lucis I2.L4.600.X IZAR II LED
Lamps: 1 x LED G6

