

IZAR III I3.L3.1500.XY

**Type:** luminaire de plafond et mural

**Abat-jour:** verre acrylique, front blanc (.92) ou noir (.93)

**Luminaire:** tôle en acier peint en blanc



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	IK 06	PM A	PM B	PM C	PM D	PM E	PM F	PM G	PM H	PM I	PM J	
26,5	3000	3670	3372	1500	80	40	M	-	P*	Q*	-	-	-	-	-	-	-	-	3200

Lucis I3.L3.1500.X IZAR LED / LDC (Polar)

**Tension:** 230V

**IK code:** IK06

**Ballaste:** Driver

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 26,5 W

**Température Couleur:** 3000 K

**Module luminous flux:** 3670 lm

**Luminaire luminous flux:** 3372 lm

**A:** 1500 mm

**B:** 80 mm

**C:** 40 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Non disponible

**Module d'urgence:** Disponible sur demande

**Contrôle Bluetooth:** Disponible sur demande

**Track system:** Non disponible

**Sádrokarton:** Non disponible

**Poids:** 3200 g

Luminaire: Lucis I3.L3.1500.X IZAR LED  
Lamps: 1 x LED G6

