



IZAR III ZLI3.L4.900.XY

**Type:** suspension lamp

**Lampshade:** acrylic glass, front white (.92) or black (.93)

**Metal parts:** white painted steel plate

**Pendant:** steel wire suspension with a transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	☺	☺	☺	☺	☺	☺
15,5	4000	2184	2003	900	80	2000	40	M	-	P*	Q*	R*	D*	2700

Lucis ZLI3.L4.900.X IZAR III LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 15,5 W

**Color temperature:** 4000 K

**Module luminous flux:** 2184 lm

**Luminaire luminous flux:** 2003 lm

**A:** 900 mm

**B:** 80 mm

**C:** 2000 mm

**D:** 40 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Available on inquiry

**Sádrokarton:** Available on inquiry

**Weight:** 2700 g

Luminaire: Lucis ZLI3.L4.900.X IZAR III LED  
Lamps: 1 x LED G6

