



ALFA S00.L1.150.XY

**Type:** ceiling and wall lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Light body:** painted steel plate RAL 9003 (.60) or RAL 9005 (.61)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 1	DALI 2	CORR	IK01	IK02	Bluetooth	Emergency module	PHASE CUT	Weight
6	3000	498	423	142	150	-	-	-	-	-	-	-	S*	800

**Voltage:** 230V

**IK code:** IK01

**CRI:** >80

**LED life:** L80/F10 50000 hours

**Watt:** 6 W

**Color temperature:** 3000 K

**Module luminous flux:** 498 lm

**Luminaire luminous flux:** 423 lm

**A:** 142 mm

**B:** 150 mm

**Dali 1:** Not available

**Dali 2:** Not available

**Corridor function:** Not available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Not available

**Track system:** Not available

**Phase-cut dimming:** Available on inquiry

**Weight:** 800 g

Lucis S00.L1.150.X ALFA LED / LDC (Polar)

Luminaire: Lucis S00.L1.150.X ALFA LED  
Lamps: 1 x LED 4038

