

POLARIS ZKS ZKS.L1.300.XY


**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80) or brass (.84)

**Pendant:** white or black self-carrying conductor reinforced with a steel wire

Driver of the luminaire is placed inside the ceiling rose.



| W    | K    | Module luminous flux lm | Luminaire luminous flux lm | A   | C    | DALI 2 | Motion sensor | Emergency | Bluetooth | Track system | Weight     |
|------|------|-------------------------|----------------------------|-----|------|--------|---------------|-----------|-----------|--------------|------------|
| 18,3 | 3000 | 2673                    | 2353                       | 300 | 2000 | M      | -             | P*        | Q*        | R*           | D* U* 2900 |

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 18,3 W

**Color temperature:** 3000 K

**Module luminous flux:** 2673 lm

**Luminaire luminous flux:** 2353 lm

**A:** 300 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Available on inquiry

**Sádrokarton:** Available on inquiry

**CRI > 90:** Available on inquiry

**Weight:** 2900 g

Lucis ZKS.L1.300.X POLARIS ZKS LED / LDC (Polar)

Luminaire: Lucis ZKS.L1.300.X POLARIS ZKS LED  
Lamps: 1 x LED G6

