

POLARIS ZL PE ZL1.P4.630.XY PE


**Type:** luminaire suspendu

**Abat-jour:** polyéthylène opal PE

**Les pièces métalliques:** acier laqué RAL 9003 (.31), RAL chrom (.77) ou chromé (.80)

**Suspension:** câbles d'acier avec câble transparent

The luminaire driver is placed right inside the luminaire (LED version).



| W    | K    | Module<br>luminous<br>flux lm | Luminaire<br>luminous<br>flux lm | A   | C    | DALI<br>2 | ☼ | ☼  | 📶  | 📄  | 🛒 |      |
|------|------|-------------------------------|----------------------------------|-----|------|-----------|---|----|----|----|---|------|
| 61,3 | 4000 | 9704                          | 8928                             | 630 | 2000 | M         | - | P* | Q* | R* | - | 8700 |

**Tension:** 230V

**Ballaste:** Driver

**IK code:** IK10

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 61,3 W

**Température Couleur:** 4000 K

**Module luminous flux:** 9704 lm

**Luminaire luminous flux:** 8928 lm

**A:** 630 mm

**C:** 2000 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Non disponible

**Module d'urgence:** Disponible sur demande

**Contrôle Bluetooth:** Disponible sur demande

**Track system:** Disponible sur demande

**Sádrokarton:** Non disponible

**Poids:** 8700 g

Lucis ZL1.P4.630.X PE POLARIS ZL PE LED / LDC (Polar)

Luminaire: Lucis ZL1.P4.630.X PE POLARIS ZL PE LED  
Lamps: 1 x LED G5

