

POLARIS ZK PE ZK.P4.630.XY PE


Type: suspension lamp

Lampshade: polyethylene opal PE

Metal parts: painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80), stainless steel (.83) or brass (.84)

Pendant: white or black self-carrying conductor reinforced with a steel wire

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Bluetooth	Track system	Weight
59,4	4000	8752	8051	630	2000	M	-	P*	Q*	-



DIALux
17.03.2023

Operator
Telephone
Fax
e-Mail

Voltage: 230V

Ballast: Driver

IK code: IK10

CRI: >90

LED life: L80/F10 50000 hours

Watt: 59,4 W

Color temperature: 4000 K

Module luminous flux: 8752 lm

Luminaire luminous flux: 8051 lm

A: 630 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 8700 g

Lucis ZK.P4.600.X PE POLARIS ZK PE LED / LDC (Polar)

Luminaire: Lucis ZK.P4.600.X PE POLARIS ZK PE LED
Lamps: 1 x LED G5

