

POLARIS ZT PE ZT.P4.500.XY PE

Type: luminaire suspendu

Abat-jour: polyéthylène opal PE

Les pièces métalliques: acier laqué RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chromé (.80), inox (.83) ou laiton (.84)

Suspension: tube

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	🚶	🚶	📶	📄	👤	
48,5	4000	7800	7176	500	1000	M	-	P*	Q*	R*	-	5800

Ballaste: Driver

IK code: IK10

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 48,5 W

Température Couleur: 4000 K

Module luminous flux: 7800 lm

Luminaire luminous flux: 7176 lm

A: 500 mm

C: 1000 mm

Dali 2: Disponible

Capteur de mouvement: Non disponible

Module d'urgence: Disponible sur demande

Contrôle Bluetooth: Disponible sur demande

Track system: Disponible sur demande

Sádrokarton: Non disponible

Poids: 5800 g

Lucis ZT.P4.500.X PE POLARIS ZL PE LED / LDC (Polar)

Luminaire: Lucis ZT.P4.500.X PE POLARIS ZL PE LED
Lamps: 1 x LED G6

