

POLARIS ZKS ZKS.L1.400.XY



Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80) or brass (.84)

Pendant: white or black self-carrying conductor reinforced with a steel wire

Driver of the luminaire is placed inside the ceiling rose.



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | C | DALI 2 | IK10 | IK15 | Bluetooth | Emergency | U* | Weight | |
|------|------|-------------------------|----------------------------|-----|------|--------|------|------|-----------|-----------|----|--------|------|
| 25,4 | 3000 | 3678 | 3274 | 400 | 2000 | M | - | P* | Q* | - | D* | U* | 4900 |

Lucis ZKS.L1.400.X POLARIS ZKS LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 25,4 W

Color temperature: 3000 K

Module luminous flux: 3678 lm

Luminaire luminous flux: 3274 lm

A: 400 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Available on inquiry

CRI > 90: Available on inquiry

Weight: 4900 g

Luminaire: Lucis ZKS.L1.400.X POLARIS ZKS LED
Lamps: 1 x LED G6

