

POLARIS ZL MAX PE ZL1.P2.770.XY PE


Type: luminaire suspendu

Abat-jour: polyéthylène opal PE

Les pièces métalliques: acier laqué RAL 9003 (.31), RAL chrom (.77) ou chromé (.80)

Suspension: câbles d'acier avec câble transparent

The luminaire driver is placed right inside the luminaire.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	IK10	IK11	Bluetooth	Track system	Sádrokarton	Poids
78,2	4000	11896	10459	770	2000	M	-	-	Q*	-	-	18000

Tension: 230V

Ballaste: Driver

IK code: IK10

ballaste: EVG

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 78,2 W

Température Couleur: 4000 K

Module luminous flux: 11896 lm

Luminaire luminous flux: 10459 lm

A: 770 mm

C: 2000 mm

Dali 2: Disponible

Capteur de mouvement: Non disponible

Module d'urgence: Non disponible

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 18000 g

Lucis ZL1.P2.770.X PE POLARIS ZL MAX PE LED / LDC (Polar)

Luminaire: Lucis ZL1.P2.770.X PE POLARIS ZL MAX PE LED
Lamps: 1 x LED G6

