

POLARIS ZL MAX PE ZL1.P2.1000.XY PE

Type: luminaire suspendu

Abat-jour: polyéthylène opal PE

Les pièces métalliques: acier laqué RAL 9003 (.31), RAL chrom (.77) ou chromé (.80)

Suspension: câbles d'acier avec câble transparent

The luminaire driver is placed right inside the luminaire.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	☼	☼	Bluetooth	☰	📦	📦
90,9	4000	13464	11856	1000	2000	M	-	-	Q*	-	-	28000

Tension: 230V

Ballaste: Driver

IK code: IK10

ballaste: EVG

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 90,9 W

Température Couleur: 4000 K

Module luminous flux: 13464 lm

Luminaire luminous flux: 11856 lm

A: 1000 mm

C: 2000 mm

Dali 2: Disponible

Capteur de mouvement: Non disponible

Module d'urgence: Non disponible

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 28000 g

Lucis ZL1.P2.1000.X PE POLARIS ZL MAX PE LED / LDC (Polar)

Luminaire: Lucis ZL1.P2.1000.X PE POLARIS ZL MAX PE LED
Lamps: 1 x LED G6

