


ZERO ZL3.K1.Z600.Y

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9006 structured

Pendant: steel wire suspension with a transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 1	DALI 2	CORR	IK	IP	BT	TS	Weight
50,8	3000	6658	5188	600	100	2000	-	M	N*	-	P*	Q*	-	8500

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 50,8 W

Color temperature: 3000 K

Module luminous flux: 6658 lm

Luminaire luminous flux: 5188 lm

A: 600 mm

B: 100 mm

C: 2000 mm

Dali 1: Not available

Dali 2: Available

Corridor function: Available on inquiry

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Weight: 8500 g

Lucis ZL3.K1.Z600 ZERO LED / LDC (Polar)

Luminaire: Lucis ZL3.K1.Z600 ZERO LED
Lamps: 1 x LED G5

