



AULA ZT ZT.AU1.L1.1200.XY

Type: luminaire suspendu

Abat-jour: verre acrylique

Suspension: tube

Le corps du luminaire et suspension: acier laqué - RAL blanc 9016 (.41), RAL 7012 (.47), RAL Argento dorato (.70), RAL Cuivre (.72), RAL Bronze (.73) ou RAL Laiton (.74)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	☺	☺	☺	☺	☺	☺
42	3000	5704	5359	1200	125	1000	50	M	-	P*	-	R*	-	4000

Lucis ZT.AU1.L1.1200.X AULA LED / LDC (Polar)

Tension: 230V

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 42 W

Température Couleur: 3000 K

Module luminous flux: 5704 lm

Luminaire luminous flux: 5359 lm

A: 1200 mm

B: 125 mm

C: 1000 mm

D: 50 mm

Dali 2: Disponible

Capteur de mouvement: Non disponible

Module d'urgence: Disponible sur demande

Contrôle Bluetooth: Non disponible

Track system: Disponible sur demande

Sádrokarton: Non disponible

Poids: 4000 g

Luminaire: Lucis ZT.AU1.L1.1200.X AULA LED
Lamps: 1 x LED G6

