


AULA ZT ZT.AU1.L2.1500.XY

**Type:** luminaire suspendu

**Abat-jour:** verre acrylique

**Suspension:** tube

**Le corps du luminaire et suspension:** acier laqué - RAL blanc 9016 (.41), RAL 7012 (.47), RAL Argento dorato (.70), RAL Cuivre (.72), RAL Bronze (.73) ou RAL Laiton (.74)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	☒	☒	☒	☒	☒	☒
51	4000	7015	6591	1500	125	1000	50	M	-	P*	-	R*	-	4800

Lucis ZT.AU1.L2.1500.X AULA LED / LDC (Polar)

**Tension:** 230V

**Ballaste:** Driver

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 51 W

**Température Couleur:** 4000 K

**Module luminous flux:** 7015 lm

**Luminaire luminous flux:** 6591 lm

**A:** 1500 mm

**B:** 125 mm

**C:** 1000 mm

**D:** 50 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Non disponible

**Module d'urgence:** Disponible sur demande

**Contrôle Bluetooth:** Non disponible

**Track system:** Disponible sur demande

**Sádrokarton:** Non disponible

**Poids:** 4800 g

Luminaire: Lucis ZT.AU1.L2.1500.X AULA LED  
Lamps: 1 x LED G6

