


POLARIS ZTR ZTR.L2.200.XY

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9016 (.41), RAL 9005 (.45), RAL Copper (.72), RAL Bronze (.73), RAL Brass (.74) or RAL Chrom (.77)

Pendant: rod



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
8,3	4000	1146	1044	200	225	1000	M	-	P*	Q*	R*	2400

Voltage: 230V

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 8,3 W

Color temperature: 4000 K

Module luminous flux: 1146 lm

Luminaire luminous flux: 1044 lm

A: 200 mm

B: 225 mm

C: 1000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Not available

Weight: 2400 g

Lucis ZTR.L2.200.X POLARIS ZTR LED / LDC (Polar)

Luminaire: Lucis ZTR.L2.200.X POLARIS ZTR LED
Lamps: 1 x LED G6

