




POLARIS S BS14.L1.200.XY

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: painted aluminium - RAL white 9016 (.41), RAL black 9005 (.45), RAL Copper (.72), RAL Bronze (.73) or RAL Brass (.74)

The ceiling version has IP44 rating of ingress protection, the wall version has IP40.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
8,3	3000	1060	967	200	140	210	M	-	-	-	-	1700

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 8,3 W

Color temperature: 3000 K

Module luminous flux: 1060 lm

Luminaire luminous flux: 967 lm

A: 200 mm

B: 140 mm

C: 210 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Not available

Track system: Not available

Sádrokarton: Not available

Weight: 1700 g

Lucis BS14.L1.200.X POLARIS S LED / LDC (Polar)

Luminaire: Lucis BS14.L1.200.X POLARIS S LED
Lamps: 1 x LED G6

