



POLARIS S BS14.L2.200.XY

**Type:** ceiling and wall lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Light body:** painted aluminium - RAL white 9016 (.41), RAL black 9005 (.45), RAL Copper (.72), RAL Bronze (.73) or RAL Brass (.74)

The ceiling version has IP44 rating of ingress protection, the wall version has IP40.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
8,3	4000	1146	1044	200	140	210	M	-	-	-	-	1700

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 8,3 W

**Color temperature:** 4000 K

**Module luminous flux:** 1146 lm

**Luminaire luminous flux:** 1044 lm

**A:** 200 mm

**B:** 140 mm

**C:** 210 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Not available

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 1700 g

Lucis BS14.L2.200.X POLARIS S LED / LDC (Polar)

Luminaire: Lucis BS14.L2.200.X POLARIS S LED  
Lamps: 1 x LED G6

