


IZAR METAL I2.L2.320.XY

Type: wall lamp

Lampshade: acrylic glass in combination with painted steel plate - RAL 9003, RAL 7021, RAL 6034, RAL 1018, RAL Copper, RAL Bronze, RAL 7023 or RAL 5009

Light body: white painted steel plate



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Emergency | Bluetooth | Track system | Weight |
|-----|------|-------------------------|----------------------------|-----|----|-----------------|--------|-----------|-----------|--------------|----------------------|
| 9,1 | 4000 | 1278 | 1111 | 320 | 80 | 40 Project 2 | M | - | - | - | DIALux 08.01.2024 |

Operator
Telephone
Fax
E-Mail

Voltage: 230V

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 9,1 W

Color temperature: 4000 K

Module luminous flux: 1278 lm

Luminaire luminous flux: 1111 lm

A: 320 mm

B: 80 mm

C: 40 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Not available

Track system: Not available

Sádrokarton: Not available

Weight: 800 g

Lucis I2.L2.320.X IZAR METAL LED / LDC (Polar)

Luminaire: Lucis I2.L2.320.X IZAR METAL LED
Lamps: 1 x LED G6

