


IZAR METAL I2.L2.600.XY'

**Type:** wall lamp

**Lampshade:** acrylic glass in combination with painted steel plate - RAL 9003, RAL 7021, RAL 6034, RAL 1018, RAL Copper, RAL Bronze, RAL 7023 or RAL 5009

**Light body:** white painted steel plate



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
20,9	4000	2806	2499	600	80	40	M	-	-	-	-	1400

Lucis I2.L2.600.X IZAR METAL LED / LDC (Polar)

**Voltage:** 230V

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 20,9 W

**Color temperature:** 4000 K

**Module luminous flux:** 2806 lm

**Luminaire luminous flux:** 2499 lm

**A:** 600 mm

**B:** 80 mm

**C:** 40 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Not available

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 1400 g

Luminaire: Lucis I2.L2.600.X IZAR METAL LED  
Lamps: 1 x LED G6

