



DAPHNE ZL ZL3.L1.D351.31Y

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.31), RAL chrom (.77)

Pendant: wire suspension with white cable



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | D | DALI 2 | IK 10 | IK 10 | Bluetooth | Emergency | Weight |
|----|------|-------------------------------|----------------------------------|-----|-----|------|-----------|-----------|----------|----------|-----------|-----------|--------|
| 16 | 3000 | 2412 | 1872 | 350 | 160 | 2000 | max. 1000 | M | - | P* | Q* | - | 3500 |

Lucis ZL3.L1.D351.X DAPHNE LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 16 W

Color temperature: 3000 K

Module luminous flux: 2412 lm

Luminaire luminous flux: 1872 lm

A: 350 mm

B: 160 mm

C: 2000 mm

D: max. 1000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 3500 g

Luminaire: Lucis ZL3.L1.D351.X DAPHNE LED
Lamps: 1 x LED G6

