



DAPHNE ZL ZL3.L2.D351.31Y

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.31), RAL chrom (.77)

Pendant: wire suspension with white cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	IK01	IK08	Bluetooth	Emergency	Weight
16	4000	2607	2052	350	160	2000	max. 1000	M	-	P*	Q*	-	3500

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 16 W

Color temperature: 4000 K

Module luminous flux: 2607 lm

Luminaire luminous flux: 2052 lm

A: 350 mm

B: 160 mm

C: 2000 mm

D: max. 1000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 3500 g

Lucis ZL3.L2.D351.X DAPHNE LED / LDC (Polar)

Luminaire: Lucis ZL3.L2.D351.X DAPHNE LED
Lamps: 1 x LED 2514

