



OMNIA O.150.K1.X

Typ: Wandleuchte

Lampenschirm: Acrylglas

Metallteile: lackiertes Stahlblech RAL 9003 (.60), RAL 9005 (.61) oder RAL 7016 (.62)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 1	DALI 2	Person Icon	Person Icon	Bluetooth	Track System	Weight
9,6	3000	1237	960	125	130	295	-	-	-	-	-	-	1000

Spannung: 230V

Vorschaltgerät: Driver

CRI: >90

LED-Lebensdauer: L80/F10 50000 Stunden

Watt: 9,6 W

Farbtemperatur: 3000 K

Module luminous flux: 1237 lm

Luminaire luminous flux: 960 lm

A: 125 mm

B: 130 mm

C: 295 mm

: Nicht Verfügbar

Dali 2: Nicht Verfügbar

Bewegungsmelder: Nicht Verfügbar

Notlichtmodul: Nicht Verfügbar

Bluetooth-Steuerung: Nicht Verfügbar

Track-System: Nicht Verfügbar

Gewicht: 1000 g

Lucis O.150.K1.X OMNIA LED / LDC (Polar)

Luminaire: Lucis O.150.K1.X OMNIA LED
Lamps: 1 x LED G5

