



OMNIA O.150.K1.X

**Type:** luminaire mural

**Abat-jour:** verre acrylique

**Les pièces métalliques:** acier laqué RAL 9003 (.60), RAL 9005 (.61) ou RAL 7016 (.62)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Handicap	Fire	Bluetooth	Track system	Weight
9,6	3000	1237	960	125	130	295	-	-	-	-	-	1000

**Tension:** 230V

**Ballaste:** Driver

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 9,6 W

**Température Couleur:** 3000 K

**Module luminous flux:** 1237 lm

**Luminaire luminous flux:** 960 lm

**A:** 125 mm

**B:** 130 mm

**C:** 295 mm

**Dali 2:** Non disponible

**Capteur de mouvement:** Non disponible

**Module d'urgence:** Non disponible

**Contrôle Bluetooth:** Non disponible

**Track system:** Non disponible

**Sádrokarton:** Non disponible

**Poids:** 1000 g

Lucis O.150.K1.X OMNIA LED / LDC (Polar)

Luminaire: Lucis O.150.K1.X OMNIA LED  
Lamps: 1 x LED G5

