




GEO ZK4.L1.G100.61Y

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9005 (.61)

Pendant: black cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 1	DALI 2	CORR	IK	IP	Bluetooth	Track	Weight
19,6	3000	2716	2320	1700	950	150	150	L	M	N*	-	-	Q*	-	5500

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 19,6 W

Color temperature: 3000 K

Module luminous flux: 2716 lm

Luminaire luminous flux: 2320 lm

A: 1700 mm

B: 950 mm

C: 150 mm

D: 150 mm

Dali 1: Available

Dali 2: Available

Corridor function: Available on inquiry

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Weight: 5500 g

Lucis ZK4.L1.G100.61_pc(4) GEO LED / LDC (Polar)

Luminaire: Lucis ZK4.L1.G100.61_pc(4) GEO LED
Lamps: 1 x LED G5

