



GEO ZK4.L2.G100.61Y

**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9005 (.61)

**Pendant:** black cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	⚡	🚪	📶	📄	👤	
18,1	4000	2912	2497	1700	950	150	150	M	-	-	Q*	-	-	5500

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 18,1 W

**Color temperature:** 4000 K

**Module luminous flux:** 2912 lm

**Luminaire luminous flux:** 2497 lm

**A:** 1700 mm

**B:** 950 mm

**C:** 150 mm

**D:** 150 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 5500 g

Lucis ZK4.L2.G100.61\_pc(4) GEO LED / LDC (Polar)

Luminaire: Lucis ZK4.L2.G100.61\_pc(4) GEO LED  
Lamps: 1 x LED G6

