


PALA SR.L1.P1.45.Y

**Type:** ceiling and wall lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9005 (.45) or with a reflective highly polished brass-coated disc (.45M)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth control	Track system	Weight
8,3	3000	1060	899	365	340	200	M	-	-	-	-	3000

Lucis SR.L1.P1.45 PALA LED / LDC (Polar)

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 8,3 W

**Color temperature:** 3000 K

**Module luminous flux:** 1060 lm

**Luminaire luminous flux:** 899 lm

**A:** 365 mm

**B:** 340 mm

**C:** 200 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Not available

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 3000 g

Luminaire: Lucis SR.L1.P1.45 PALA LED  
Lamps: 1 x LED G6

