


TENDO PMMA S26.K2.TEZ2.Y

Typ: Decken- und Wandleuchte

Lampenschirm: Acrylglas PMMA

Leuchte: weiß lackiertes Stahlblech



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	IK 40	LED	CRI >90	TW	Weight	
18,1	4000	2491	1790	300	260	70	20	M	-	-	Q*	-	-	1200

Spannung: 230V

IK Code: IK10

Vorschalgerät: Driver

CRI: >90

LED-Lebensdauer: L80/F10 50000 Stunden

Watt: 18,1 W

Farbtemperatur: 4000 K

Module luminous flux: 2491 lm

Luminaire luminous flux: 1790 lm

A: 300 mm

B: 260 mm

C: 70 mm

D: 20 mm

Dali 2: Verfügbar

Bewegungsmelder: Nicht Verfügbar

Notlichtmodul: Nicht Verfügbar

Bluetooth-Steuerung: Verfügbar auf Anfrage

Track-System: Nicht Verfügbar

Sádrokarton: Nicht Verfügbar

Gewicht: 1200 g

Lucis S26.K2.TEZ2 TENDO LED / LDC (Polar)

Luminaire: Lucis S26.K2.TEZ2 TENDO LED
Lamps: 1 x LED G5

