

POLARIS ZKS.P ZKS.P5.400.XM


Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80) or brass (.84)

Pendant: white or black self-carrying conductor reinforced with a steel wire

POLARIS ZKS.P luminaires are ****supplied as DALI dimmable**** as standard equipment. Driver of the luminaire is placed inside the ceiling rose.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Bluetooth	Emergency module	Weight	
48,5	3000	7216	6494	400	2000	M	-	P*	Q*	-	6000

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 48,5 W

Color temperature: 3000 K

Module luminous flux: 7216 lm

Luminaire luminous flux: 6494 lm

A: 400 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 6000 g

Lucis ZKS.P5.400.X POLARIS ZKS.P LED / LDC (Polar)

Luminaire: Lucis ZKS.P5.400.X POLARIS ZKS.P LED
Lamps: 1 x LED G6

