

MAIA B PMMA ZK.L1B.M800.Y PA

Type: suspension lamp

Lampshade: acrylic glass PMMA

Metal parts: white painted steel plate

Pendant: self-supporting white cable reinforced with a steel wire

The luminaire driver is placed right inside the luminaire.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 1	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight
109,9	3000	14468	11535	200	800	2000	-	M	-	-	-	R*	5400

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 109,9 W

Color temperature: 3000 K

Module luminous flux: 14468 lm

Luminaire luminous flux: 11535 lm

A: 200 mm

B: 800 mm

C: 2000 mm

Dali 1: Not available

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Not available

Track system: Available on inquiry

Weight: 5400 g

Lucis ZK.L1B.M800 PA MAIA LED / LDC (Polar)

Luminaire: Lucis ZK.L1B.M800 PA MAIA LED
Lamps: 1 x LED G5

