

MAIA B PMMA ZK.L2B.M620.Y PA


Type: suspension lamp

Lampshade: acrylic glass PMMA

Metal parts: white painted steel plate

Pendant: self-supporting white cable reinforced with a steel wire

The luminaire driver is placed right inside the luminaire.



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Motion sensor | Emergency module | Bluetooth | Track system | Weight | |
|------|------|-------------------------|----------------------------|-----|-----|------|--------|---------------|------------------|-----------|--------------|--------|------|
| 43,9 | 4000 | 6312 | 5033 | 150 | 620 | 2000 | M | - | P* | - | R* | D* | 3400 |

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 43,9 W

Color temperature: 4000 K

Module luminous flux: 6312 lm

Luminaire luminous flux: 5033 lm

A: 150 mm

B: 620 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Not available

Track system: Available on inquiry

Sádrokarton: Available on inquiry

Weight: 3400 g

Lucis ZK.L2B.M620 PA MAIA LED / LDC (Polar)

Luminaire: Lucis ZK.L2B.M620 PA MAIA LED
Lamps: 1 x LED G5

