

MAIA B PMMA ZK.L2B.M800.Y PA


**Type:** suspension lamp

**Lampshade:** acrylic glass PMMA

**Metal parts:** white painted steel plate

**Pendant:** self-supporting white cable reinforced with a steel wire

The luminaire driver is placed right inside the luminaire.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 1	DALI 2	Motion sensor	Bluetooth	Track system	Weight
109,9	4000	15157	12084	200	800	2000	-	M	-	-	R*	5400

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 109,9 W

**Color temperature:** 4000 K

**Module luminous flux:** 15157 lm

**Luminaire luminous flux:** 12084 lm

**A:** 200 mm

**B:** 800 mm

**C:** 2000 mm

: Not available

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Not available

**Track system:** Available on inquiry

**Weight:** 5400 g

Lucis ZK.L2B.M800 PA MAIA LED / LDC (Polar)

Luminaire: Lucis ZK.L2B.M800 PA MAIA LED  
Lamps: 1 x LED G5

