


SEMILUNA ZT4.L1.S200.XY

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.60), RAL 9005 (.61), RAL Bronze (.73) or RAL Chrom (.77)

Pendant: rod



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	IK01	Q*	Weight
28,8	3000	4386	2632	1050	200	750	M	-	-	12600

Lucis ZT4.L1.S200.X_pc(4) SEMILUNA LED / LDC (Polar)

Luminaire: Lucis ZT4.L1.S200.X_pc(4) SEMILUNA LED
Lamps: 1 x LED G6

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 28,8 W

Color temperature: 3000 K

Module luminous flux: 4386 lm

Luminaire luminous flux: 2632 lm

A: 1050 mm

B: 200 mm

C: 750 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 12600 g

