



SEMILUNA ZT4.L1.S200.XY

Type: luminaire suspendu

Abat-jour: verre blanc, soufflé de manière artisanale, à trois couches, satin opale mat

Les pièces métalliques: acier laqué RAL 9003 (.60), RAL 9005 (.61), RAL Bronze (.73) ou RAL Chrom (.77)

Suspension: tube



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	IK01	Q*	Weight
28,8	3000	4386	2632	1050	200	750	M	-	-	12600

Lucis ZT4.L1.S200.X_pc(4) SEMILUNA LED / LDC (Polar)

Luminaire: Lucis ZT4.L1.S200.X_pc(4) SEMILUNA LED
Lamps: 1 x LED G6

Tension: 230V

IK code: IK01

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 28,8 W

Température Couleur: 3000 K

Module luminous flux: 4386 lm

Luminaire luminous flux: 2632 lm

A: 1050 mm

B: 200 mm

C: 750 mm

Dali 2: Disponible

Capteur de mouvement: Non disponible

Module d'urgence: Non disponible

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 12600 g

