


SEMILUNA ZT6.L2.S200.XY

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.60), RAL 9005 (.61), RAL Bronze (.73) or RAL Chrom (.77)

Pendant: rod



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	IK 01	IP 20	Bluetooth	Emergency	Weight
43,3	4000	7074	4244	1050	200	850	M	-	-	Q*	-	17400

Lucis ZT6.L2.S200.X_pc(6) SEMILUNA LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 43,3 W

Color temperature: 4000 K

Module luminous flux: 7074 lm

Luminaire luminous flux: 4244 lm

A: 1050 mm

B: 200 mm

C: 850 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 17400 g

Luminaire: Lucis ZT6.L2.S200.X_pc(6) SEMILUNA LED
Lamps: 1 x LED G6

