


SEMILUNA ZT.L1.S115.XY

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.60), RAL 9005 (.61), RAL Bronze (.73) or RAL Chrom (.77)

Pendant: rod



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 1	DALI 2	CORR	IK	IP	Bluetooth	Emergency	Weight
5,8	3000	679	407	115	1000	L	M	N*	-	P*	Q*	R*	1600

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 5,8 W

Color temperature: 3000 K

Module luminous flux: 679 lm

Luminaire luminous flux: 407 lm

A: 115 mm

C: 1000 mm

Dali 1: Available

Dali 2: Available

Corridor function: Available on inquiry

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Weight: 1600 g

Lucis ZT.L1.S115.X SEMILUNA LED / LDC (Polar)

Luminaire: Lucis ZT.L1.S115.X SEMILUNA LED
Lamps: 1 x LED G5

