


SEMILUNA ZT.L1.S150.XY

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.60), RAL 9005 (.61), RAL Bronze (.73) or RAL Chrom (.77)

Pendant: rod



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | C | DALI 2 | Motion sensor | Panic button | Bluetooth | Emergency module | Weight (g) |
|-----|------|-------------------------|----------------------------|-----|------|--------|---------------|--------------|-----------|------------------|------------|
| 6,2 | 3000 | 804 | 482 | 150 | 1000 | M | - | P* | Q* | - | 1700 |

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 6,2 W

Color temperature: 3000 K

Module luminous flux: 804 lm

Luminaire luminous flux: 482 lm

A: 150 mm

C: 1000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 1700 g

Lucis ZT.L1.S150.X SEMILUNA LED / LDC (Polar)

Luminaire: Lucis ZT.L1.S150.X SEMILUNA LED
Lamps: 1 x LED G6

