


SEMILUNA ZT.L2.S200.XY

**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9003 (.60), RAL 9005 (.61), RAL Bronze (.73) or RAL Chrom (.77)

**Pendant:** rod



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Panic button	Bluetooth	Emergency module	Weight
8,1	4000	1179	708	200	1000	M	-	P*	Q*	-	2200

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 8,1 W

**Color temperature:** 4000 K

**Module luminous flux:** 1179 lm

**Luminaire luminous flux:** 708 lm

**A:** 200 mm

**C:** 1000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 2200 g

Lucis ZT.L2.S200.X SEMILUNA LED / LDC (Polar)

Luminaire: Lucis ZT.L2.S200.X SEMILUNA LED  
Lamps: 1 x LED G6

