

CAPSULE ZL.L1.C.XY

**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate – RAL 7012 (.47), RAL 9003 (.60), RAL 9005 (.61), RAL 3012 (.75) or RAL 6011 (.76)

**Pendant:** wire suspension with white or black cable

The beam angle of the lighting source can be changed by fixation of the lampshade, "see positions A, B or C." : <https://www.lucis.eu/obrazky/obrazek-12462.png>

The position of the glass sphere does not change, only the level of the metal shade can be adjusted.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 1	DALI 2	GORR	Staircase	Door	Bluetooth	Track system	Weight
7,4	3000	992	590	220	350	2200	L	M	N*	-	-	Q*	R*	3500

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 7,4 W

**Color temperature:** 3000 K

**Module luminous flux:** 992 lm

**Luminaire luminous flux:** 590 lm

**A:** 220 mm

**B:** 350 mm

**C:** 2200 mm

**Dali 1:** Available

**Dali 2:** Available

**Corridor function:** Available on inquiry

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Available on inquiry

**Track system:** Available on inquiry

**Weight:** 3500 g

Lucis ZL.L1.C.X CAPSULE LED / LDC (Polar)

Luminaire: Lucis ZL.L1.C.X CAPSULE LED  
Lamps: 1 x LED G5

