

CAPSULE ZL.L2.C20.XY

Type: suspension lamp


Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted aluminum – RAL 7012 (.47), RAL 9003 (.60), RAL 9005 (.61), RAL 3012 (.75) or RAL 6011 (.76)

Pendant: wire suspension with white or black cable

The beam angle of the lighting source can be changed by fixation of the lampshade, see positions A, B or C.

The position of the glass sphere does not change, only the level of the aluminum shade can be adjusted.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Emergency sensor	Emergency stop	Bluetooth	Track system	Weight	
8,1	4000	1179	703	220	350	2000	M	-	-	Q*	R*	D*	3500

Lucis ZL.L2.C20.X CAPSULE LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 8,1 W

Color temperature: 4000 K

Module luminous flux: 1179 lm

Luminaire luminous flux: 703 lm

A: 220 mm

B: 350 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Available on inquiry

Weight: 3500 g

Luminaire: Lucis ZL.L2.C20.X CAPSULE LED
Lamps: 1 x LED G6

