

PRIMA BS34.K2.P34.XY

Type: luminaire de plafond et mural

Abat-jour: verre blanc, soufflé de manière artisanale, à trois couches, satin opale mat

Luminaire: aluminium laqué RAL 9016 (.41), RAL 9005 (.45), RAL Argento dorato (.70), RAL Bronze (.73) ou RAL Laiton (.74)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	Emergency lighting	Emergency lighting	Bluetooth	Track system	Weight
36	4000	4659	3122	340	120	M	O*	P*	Q*	-	2500

Tension: 230V

IK code: IK01

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 36 W

Température Couleur: 4000 K

Module luminous flux: 4659 lm

Luminaire luminous flux: 3122 lm

A: 340 mm

B: 120 mm

Dali 2: Disponible

Capteur de mouvement: Disponible sur demande

Module d'urgence: Disponible sur demande

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 2500 g

Lucis BS34.K2.P34.X PRIMA LED / LDC (Polar)

Luminaire: Lucis BS34.K2.P34.X PRIMA LED
Lamps: 1 x LED G5

