


**PRIMA** BS44.K3.P44.XY

**Type:** luminaire de plafond et mural

**Abat-jour:** verre blanc, soufflé de manière artisanale, à trois couches, satin opale mat

**Luminaire:** aluminium laqué RAL 9016 (.41), RAL 9005 (.45), RAL Argento dorato (.70), RAL Bronze (.73) ou RAL Laiton (.74)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	Emergency lighting	Emergency lighting	Bluetooth	Track system	Weight	
29	3000	3945	2643	440	130	M	O*	P*	Q*	-	-	4400

**Tension:** 230V

**IK code:** IK01

**Ballaste:** Driver

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 29 W

**Température Couleur:** 3000 K

**Module luminous flux:** 3945 lm

**Luminaire luminous flux:** 2643 lm

**A:** 440 mm

**B:** 130 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Disponible sur demande

**Module d'urgence:** Disponible sur demande

**Contrôle Bluetooth:** Disponible sur demande

**Track system:** Non disponible

**Sádrokarton:** Non disponible

**Poids:** 4400 g

Lucis BS44.K3.P44.X PRIMA LED / LDC (Polar)

Luminaire: Lucis BS44.K3.P44.X PRIMA LED  
Lamps: 1 x LED G5

