


PRIMA BS44.K4.P44.XY

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: painted aluminium RAL 9016 (.41), RAL 9005 (.45), RAL Argento dorato (.70), RAL Bronze (.73) or RAL Brass (.74)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
29	4000	4133	2769	440	130	M	O*	P*	Q*	-	4400

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 29 W

Color temperature: 4000 K

Module luminous flux: 4133 lm

Luminaire luminous flux: 2769 lm

A: 440 mm

B: 130 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 4400 g

Lucis BS44.K4.P44.X PRIMA LED / LDC (Polar)

Luminaire: Lucis BS44.K4.P44.X PRIMA LED
Lamps: 1 x LED G5

